

MIG200 PFC LCD



Features:

- Rugged, robust, and industrial look with ergonomic design
- Color LCD control panel
- **Intelligent synergic control**
- Adaptable wide voltage range
- **Smart Lift TIG**
- Consistent and efficient MIG spot welding performance
- Flexible remote control solutions
- Power factor correction (PFC), generator-friendly
- Quick factory reset; auto sleep mode
- Compatible with MIG digital torch, spool gun and pull-push torch
- LED inside wire feeder cabinet; handy accessory storage slot
- On demand fan
- Trolley with cylinder holder
- Voltage Reduction Device (VRD)
- Key power electronic component protection
- Overcurrent, overheat, overvoltage protection



Specifications:

		MIG200 PFC LCD N2S53	
Input power		AC95~265 V, 50/60 Hz	
Open circuit voltage		115 V	230 V
		68 V	
MIG	Rated input current	38.1 A	32.8 A
	Rated input power capacity	4.4 kVA	7.5 kVA
	Output current range	30~140 A	30~200 A
	Rated duty cycle	30%	
	Wire feed speed	2~12 m/min	2~16 m/min
	Wire spool size	D300	
MMA	Rated input current	28.3 A	24.8 A
	Rated input power capacity	3.2 kVA	5.7 kVA
	Output current range	20~110 A	20~180 A
	Rated duty cycle	30%	
TIG	Rated input current	24.2 A	19.3 A
	Rated input power capacity	2.8 kVA	4.4 kVA
	Output current range	5~140 A	5~200 A
	Rated duty cycle	30%	
Efficiency		>80%	
Power factor		0.99	
Idle state power		<50 W	
Protection class		IP23S	
Insulation class		H	
Dimensions L×W×H		920×480×755 mm	
Net weight		41.9 kg	



Standard Accessories

- 3M MB-15 MIG torch
- 3M earth clamp
- 1 pc quick socket
- 2 pcs hose clamps

